



**Frequent Deadheads?
Stay cool with
WhitSlide® Extreme.**

Superior performance. Exceptional wear protection.

SLIDE LUBRICANT



With more than 120 years of experience in the lubricant business, Whitmore continues to set performance standards for the industry's toughest and most demanding applications. Now, Whitmore introduces WhitSlide® Extreme, our most recent innovation in slide lubrication and one that offers extended slide life, reduced downtime, less maintenance and more production.

WhitSlide Extreme uses the same special anti-wear technology we use in our premium enclosed gear oils. A new additive combination produces remarkable

synergy. In fact, in Four Ball testing with the maximum 800kg weld point the machine can withstand, WhitSlide Extreme scored a wear scar diameter of 0.33mm, rarely achieved by any lubricant.

Formulated using the same high viscosity base material as its predecessor, WhitSlide Extreme forms a tenacious coating on sliding surfaces. It smooths areas of metal-to-metal contact under high loads, reduces friction and heat and minimizes deadhead delays due to overheating. WhitSlide Extreme does not contain any heavy metal additives and uses an ozone-safe, non-chlorinated solvent.

Engineered for use on the walking mechanism slides of Bucyrus 2500 series draglines, it's ideal for heavily loaded bushings and can also be used on new open gears as a base coat, helping grease-type open gear lubricants stick to the metal.

- **EXTENDS SLIDE LIFE** – synergistic blend of extreme pressure and antiwear additives promote optimum lubrication over long walks.
- **KEEPS THINGS COOL** – reduced friction and heat means fewer stops for cooling.
- **SAFE TO USE** – high flash point solvent, no heavy metals, ozone-safe.

WHITSLIDE
EXTREME

whitmores.com
800.699.6318

930 Whitmore Drive, Rockwall, TX, 75087

An ISO 9001 and ISO 14001 registered company

