

GearMate® 1000

MULTISERVICE OPEN GEAR LUBRICANT

Whitmore's GearMate® 1000 is specially formulated for use on open gears and other severe applications on draglines, mining shovels, ball mills and kilns.

Whitmore's GearMate® 1000 contains a high molecular weight polymer extender that resists drying, oxidation, and thermal decomposition. This is extremely helpful in areas of high dust contamination or when typical weather conditions can cause peeling and flaking from sticks, gears, and circle rails. Whitmore's blend of solid and oil-soluble anti-wear additives provides superior load carrying ability and high performance wear resistance in an environmentally safe package.

Whitmore's GearMate® 1000 has a thickener structure that inherently resists emulsification with water and has excellent mechanical and thermal stability. The low temperature capabilities allow the lubricant film to maintain its adhesive characteristics and durable protection under the most demanding conditions.

Meets the requirements of Caterpillar specification SD 4713. "Super Heavy" is suitable for CAT Shovel Hoist Drum Gears (specification SD 4713 revision June 2011).

BENEFITS:

- **TCLP-SAFE** - passes the EPA Toxicity Characteristic Leaching Procedure. This means that the product is free of heavy metals and ozone-depleting solvents.
- **WILL NOT EMULSIFY IN WATER** - ideal for applications and components exposed to rain, ice, and snow.
- **EXTREME LOAD-CARRYING ABILITY** - protects during shock loading against scuffing and seizure.
- **REDUCED INVENTORY** – in many climates a single grade can be used year-round.

APPLICATIONS:

Whitmore's GearMate® 1000 is recommended for a variety of applications on mining draglines and shovels including open gears, sticks, circle rails and rollers, and bushings and large, heavily loaded bearings.

GearMate® 1000 is also highly recommended for use on open gears of kilns and ball mills.

Approved by KOMATSU.

ASTM #		TYPICAL CHARACTERISTICS				
		Arctic	Light	Heavy	Extra Heavy	Super Heavy
	NLGI Grade	00-000	0-00	0	1	0-1
D-445	Kinematic Viscosity (Base Oil with Polymer) cSt @ 40°C	700	1,900	4,123	3,700	6,500
	cSt @ 100°C	--	--	165	120	254
Gardner Method	Density , lb/gal @ 60°F (15.5°C)	7.50	8.38	8.33	8.55	8.55
	Specific Gravity , g/cc @ 60°F (15.5°C)	0.9010	1.0060	1.0002	1.0300	1.0300
D-92	Flash Point , Cleveland Open Cup Base Oil, °F (°C)	400 (204)	400 (204)	400 (204)	400 (204)	400 (204)
	Finished Product with Solvent, °F (°C)	250 (121)	250 (121)	No Solvent	No Solvent	No Solvent
D-2596	Four Ball EP Weld Point, kg	800	1000	1000	1000	1000
D-2266	Four Ball Wear Scar Width, mm	0.7	0.7	0.7	0.7	0.7
D-1743	Rust Test	Pass	Pass	Pass	Pass	Pass
	Thickener Type	Lithium	Lithium	Lithium	Lithium	Lithium
	Usable Temperature Range , °F (°C)	-30 (-34) to 104 (40)	-15 (-26) to 104 (40)	10 (-12) to 250 (121)	30 (-1) to 250 (121)	30 (-1) to 250 (121)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Shuttle Tanks	Drums	Kegs	Pails	Aerosol Cans
---------------	-------	------	-------	--------------

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318
An ISO 9001 and ISO 14001 registered company • www.whitmores.com

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.



Scan QR code to link to web version