

TECHNICAL DATA SHEET

PF-35™ Oil For Hump Yards and Wheel Mounting

PF-35TM is a top-of-rail product specifically designed to provide optimum friction at the wheel-rail interface at hump yards. PF-35TM substantially reduces noise and wear. It ensures that cars roll freely and prevents stop-shorts.

PF-35™ contains no solvents, water or metallic additives. It will not corrode holding tanks, pumps or other applicator components.

PF-35™ is based on white mineral oil that has been highly refined, removing sulfur and other contaminants. This type of oil is inherently biodegradable.

BENEFITS:

- WEAR Reduces creep, hunting (also known as yaw), and corrugations.
- NOISE Stops or substantially reduces noise
- ALL SEASON This grade provides year-round use in many areas.
- SAFE contains no heavy metals, petroleum solvent or hazardous ingredients.

APPLICATIONS:

PF-35™ optimizes friction at the wheel / rail interface. It is suitable for use in hump yards and on both freight and transit rail.

PF-35 $^{\text{TM}}$ is also useful as a switch plate lubricant, particularly where there is contamination from sand or grinding particles.

PF-35[™] All Season grade is suitable for use in wheel mounting.

CHARACTERISTICS			
Grade Name	PF-35™	PF-35™ All Season	
Appearance	Clear with slight yellow tint	Blue fluid	
Rust Test (ASTM 665)	Pass	Pass	
Density, lb/gal @ 60°F	7.20	7.00	
Lowest Usable Temperature, °F (°C)	0°F (-18°C)	-25° F (-31°C)	

PACKAGING

Non-returnable Totes	Drums	Pails	
-------------------------	-------	-------	--

For warranty information, scan the QR code. You can also email us at sales@whitmores.com
Or write to the Sales Department at the address below.

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318
An ISO 9001 and ISO 14001 registered company • www.whitmores.com

