



DECATHLON™ GOLD GEAR LUBRICANT

Decathlon™ Gold is the ultimate solution to the problem of lubricating open gears and very slow moving enclosed gears. It is clean, environmentally-friendly, easy to work with, and it protects even the most heavily loaded gears.

Traditionally, open gears on kilns, ball mills and dryers have been lubricated using asphaltic products. These products are dark and messy, and disposing of the waste is sometimes difficult. Decathlon™ Gold provides the same level of protection to the gears as asphaltic lubricants, but is a versatile product that is light in color.

Decathlon™ Gold may be applied using a spray system, such as is manufactured by Lincoln or Farval. It may also be applied from a sump, where the pinion drags through the lubricant, or an idler wheel applies lubricant to the pinion. It may also be continuously pumped directly onto the gears.

Decathlon™ Gold contains no solid additives. It can be filtered without loss of additives.

Decathlon™ Gold contains no hazardous materials and may be disposed of in the same manner as any spent oil.

BENEFITS:

- SAFE - Contains no hazardous materials.
- CLEAN - Light golden color.
- EASY - Can be applied by spray, dip or continuous pump.
- EFFECTIVE - Protects gears under severe load and shock load
- NO SOLID ADDITIVES - Can be filtered for longer service life.

APPLICATIONS:

Decathlon™ Gold is specifically formulated to protect heavily loaded gears on kilns, ball mills, dryers, and pelletizers. Also recommended for use on slideways, including crane slides. Decathlon™ Gold can be used to lubricate wire ropes and large chains. Provides good resistance to water.

Decathlon™ Gold is suitable for use at temperatures down to 20°F (-7°C). In applications where the oil temperature could drop below this level it may be necessary to apply heat. Consult Whitmore's Technical Service Department for further information.

May also be used in enclosed gearboxes that call for an extremely viscous gear oil.

| ASTM # | | TYPICAL CHARACTERISTICS | |
|-----------------------|---|-------------------------|--------------|
| | | Gold | Gold Heavy |
| | ISO Grade | 3200 | N/A |
| D-445 | Kinematic Viscosity cSt @ 40°C cSt @ 100°C | 3,260 176 | 5,202 215 |
| D-2270 | Viscosity Index | 155 | 147 |
| D-97 | Pour Point, °F (°C) | 30 (-1) | 35 (2) |
| Gardner Method | Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C) | 7.50 0.90 | 7.58 0.91 |
| D-92 | Flash Point, °F (°C) Cleveland Open Cup | >390 (>199) | >400 (>204) |
| D-2783 | Four Ball EP Weld Point, kg | 620 | 620 |
| D-4172 | Four Ball Wear Scar Width, mm @ 40 kgf | 0.60 | 0.40 |
| D-665 | Rust Test Distilled Water | Pass | Pass |
| D-130 | Copper Strip Corrosion 212°F (100°C) @ 3 hr | 1B | 1B |
| OEM Standard | Low Temperature Pumpability, Lincoln Ventmeter @ 400 psi, °F (°C) | 20 (-7) | 35 (2) |

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

| | | |
|---------------|-------|-------|
| Shuttle Tanks | Drums | Pails |
|---------------|-------|-------|

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108

ISO: 9001/14001/TS 16949 Registered Company • <http://www.whitmores.com>

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.