



TECHNICAL DATA SHEET

DECATHLON™ CCL CONVEYOR CHAIN LUBRICANT

Decathlon™ CCL oils are fully synthetic chain lubricants for E-Coat paint lines and water-based paint systems. These adherent lubricants were developed for chain lubrication of overhead and floor conveyors where lubricants might get into the paint bath. Wear is avoided by the presence of special antiwear additives.

Decathlon™ CCL lubricants completely dissolve in water and in water soluble paints. In contrast to conventional products, lubricant residues do not affect the paint bath. There is no formation of fish eyes, craters, pinholes, stains, or rough surfaces.

Decathlon™ CCL will substantially reduce lubricant consumption, lowering cost per operating hour and reducing service intervals for maintenance downtime.

BENEFITS:

- REDUCES CONSUMPTION - allows for longer application intervals.
- ANTIWEAR FORMULA - reduces wear in chain links, pins, and bushing areas without the use of solid lubricants.
- PROTECTS - against rust and corrosion.
- SMOOTHER & QUIETER - chains run smoother and quieter.
- OPERATING RANGE – normal ambient up to 375°F (190°C).

APPLICATIONS:

Decathlon™ CCL is ideal for chain drives of all sizes. Decathlon™ CCL may either be sprayed, injected, or dripped onto the chain.

ASTM #	Product Name	TYPICAL CHARACTERISTICS	
		CCL 150	CCL 220
D-445	ISO Grade	150	220
	Kinematic Viscosity cSt @ 40°C	148	226
	cSt @ 100°C	27	41
D-2161	Saybolt Viscosity SUS @ 100°F	715	1,094
	SUS @ 210°F	130	200
	Viscosity Index	228	236
D-2270	Pour Point, °F (°C)	-44 (-42)	-52 (-47)
Gardner Method	Density, lb/gal @ 60°F (15.5°C)	8.79	8.74
	Specific Gravity, g/cc @ 60°F (15.5°C)	1.055	1.049
	Flash Point, °F (°C) Cleveland Open Cup	440 (227)	440 (227)
D-4172	Four Ball Wear, Scar Width, mm @ 40 kgf	0.32	0.32
D-665	Rust Test Distilled Water	Pass	Pass
	Conradson Carbon Residue, % Loss	0.32	0.33
D-189	Thin Film Evaporation, % Loss @ 355°F (179°C) @ 6 hrs	4.12	3.38
D-972	Appearance	Clear Transparent	Clear Transparent

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Nonreturnable Totes	Drums	Pails
------------------------	-------	-------

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>
Performance Under Pressure Since 1893

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.