

DET 900 NON-REACTIVE GREASE

Whitmore's DET 900 is a stable, nonflammable, chemically inert grease designed for use in long life and sealed-for-life applications. It is inert to virtually all chemicals used in industry, is insoluble in most solvents, and relatively stable to radiation when compared to conventional lubricants.

This product is biologically inert and offers superior resistance to "Lewis acids," found in semiconductor manufacturing.

Whitmore's DET 900 will prove serviceable for long periods at continuous temperatures up to 400°F (204°C) with minimal re-lubrication. DET 900 can withstand higher temperatures (up to 575°F or 300°C). At 575°F re-lubrication is needed approximately every 8 to 12 hours.

Ensure adequate ventilation when used at or above 535°F (280°C)

Compatibility with elastomeric seal materials and plastics is excellent. This includes Buna N, Butyl 325, Neoprene, Nylon, and Teflon. The limiting factor when using this grease is the thermal stability of the elastomer or plastic.

BENEFITS:

- **LOW EVAPORATION** - compared to conventional synthetic greases, an increase in lubricant life of 5 to 10 times can be achieved.
- **CHEMICAL RESISTANCE** - provides protection against most aggressive chemicals that degrade conventional lubricants.
- **NONFLAMMABLE AND INERT** - depending on the specific chemicals involved, this grease can be considered for use in facilities that manufacture corrosive chemicals. Consult Whitmore's Technical Services Department before using.
- **PAINT COMPATIBLE** - since it is silicone-free, Whitmore's DET 900 EP 2 is suitable for use in high temperature paint oven bearings.
- **WIDE TEMPERATURE RANGE** – can be used up to 575°F (300°C) with adequate re-lubrication and ventilation.
- **ANTI-CORROSION** - does not contain chlorine and will not promote chloride-induced corrosion.

APPLICATIONS:

Designed for use in any grease-lubricated applications where high temperatures, chemicals, or radiation create difficulties or where long lubricant life is required.

Typical applications include bearings on hot air blowers, bearings on oven conveyors, and fan bearings on textile machines. Suitable for use in film stretching machines and will not react with plastic film.

Suitable for use in systems that handle aliphatic, aromatic, or chlorinated hydrocarbons, gasoline, ketone, alcohol, ethers, or water.

Partially soluble in trichlorotrifluoroethane. For more information, call Whitmore's Technical Service Department at 800-699-6318.

ASTM #	Grade	TYPICAL CHARACTERISTICS	
		EP 1	EP 2
D-217	Cone Penetration (Worked)	310-340	265-295
D-445	Kinematic Viscosity (Base Oil)		
	cSt @ 40°C	510	510
	cSt @ 100°C	47	47
D-2270	Viscosity Index (Base Oil)	134	134
Gardner Method	Density, lb/gal @ 77°F (25°C)	16.875	16.570
D-1298	Specific Gravity	2.02	1.99
D-2596	Four Ball EP		
	Weld Point, kg	>800	>800
D-4048	Copper Strip Corrosion for Greases		
	212°F (100°C) @ 3 hrs	1A	1A
	Oil Type	Perfluoropolyether (PFPE)	Perfluoropolyether (PFPE)
	Thickener Type	Polytetrafluoroethylene (PTFE)	Polytetrafluoroethylene (PTFE)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Cartridges
(50 per case)

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108

An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>

Performance Under Pressure Since 1893

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.