

GearMate® MULTI-SERVICE LUBRICANT

Whitmore's GearMate® Multi-Service Lubricant meets the EPA Toxicity Characteristic Leaching Procedure (TCLP) and is characterized as TCLP-SAFE.

GearMate® was developed in response to environmental and worker safety issues, while protecting the user from the potentially high cost of disposal. GearMate® combines high performance and year-round operating utility with an environmentally safe performance system, free of solvents and TCLP heavy metals.

GearMate® generates a tough, durable film on metal surfaces which resists pound-out and sling off. GearMate® also contains graphite and MoS₂ to help protect expensive parts during boundary lubrication conditions.

Lubrication and maintenance of draglines, mining shovels, track drills and other mining machinery can be simplified by the use of GearMate®. Open gears and many bearings can benefit from the use of GearMate®, allowing lubricant inventories to be reduced.

BENEFITS:

- **TCLP-SAFE** - passes EPA Toxicity Characteristic Leaching Procedure which reduces disposal costs.
- **LOWERS OPERATING TEMPERATURES** - extends gear life, reduces operating expenses.
- **CONTAINS SOLID FILM LUBRICANTS** - (MoS₂ and graphite) durable film prevents metal-to-metal contact and reduces wear.
- **-45°F (-43°C) PUMPABILITY** - one product for year-round use simplifies lubrication.

APPLICATIONS:

GearMate® is ideal for exposed parts on mining equipment such as open gears, swing racks, house rails and rollers, shovel dipper sticks, drum laggings, as well as mobile equipment pins and bushings. It is suitable for many heavily loaded bushings and bearings operating at or below 150,000 DN.

To calculate the DN factor of a bearing, use the following:

$$DN = dm \times RPM$$

$$\text{Where } dm = (I.D + O.D) \div 2$$

ASTM #		TYPICAL CHARACTERISTICS		
		Light	Medium	Heavy
D-3-2983	Viscosity (Brookfield Viscometer) Spindle 6 @ 100 rpm @ 50°F (10°C), cps Spindle 6 @ 5 rpm @ 50°F (10°C), cps Spindle 7 @ 5 rpm @ 50°F (10°C), cps	2,500	60,000	250,000
Gardner Method D-92	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C) Flash Point, °F (°C) Cleveland Open Cup (Base Oils)	8.37 1.005 >230 (>110)	8.08 0.970 >230 (>110)	8.26 0.992 >230 (>110)
D-2509 (Modified) D-2596	Timken Step Test, lb Four Ball EP Weld Point, kg	>81 500	>81 500	>81 500
D-4048 (Modified) OEM Standard	Copper Strip Corrosion 212°F (100°C) @ 3 hr Low Temperature Pumpability, Lincoln Ventmeter @ 400 psi, °F (°C) Operating Range, °F	1B -45 (-43) -45 (-43) to 265 (129)	1B 0 (-18) 0 (-18) to 280 (138)	1B 15 (-9) 15 (-9) to 280 (138)
US Steel Grease Mobility Test	Solid Lubricants Grease Mobility 150 psi @ °F, g/min.	Graphite/MoS ₂ 56.5	Graphite/MoS ₂ 37.0	Graphite/MoS ₂ 1.7

* GearMate® Medium & Heavy are not recommended for use in enclosed gear cases.

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Shuttle Tanks	Drums	Kegs	Pails
---------------	-------	------	-------

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>
Performance Under Pressure Since 1893

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.