



TECHNICAL DATA SHEET

OPEN CHAIN LUBRICANT

Whitmore's Open Chain Lubricant is specifically formulated to meet the exacting lubrication requirements of chain drives. Its penetrating action draws the lubricant to the pins and bushings of a chain where lubrication is most needed. It quickly displaces moisture and contaminants, while preventing rust and corrosion.

Whitmore's Open Chain Lubricant is also available in an aerosol spray container. The solvent propellant has been removed, making Open Chain Lubricant environmentally safer and TCLP-SAFE.

BENEFITS:

- PROTECTS - against rust and corrosion.
- IMPROVES HOUSEKEEPING - less sling-off.
- SMOOTHER AND QUIETER - chains run smoother and quieter.
- APPLICATION - applied manually or via automatic systems.
- OPERATING RANGE – From -25°F (-32°C) to 200°F (95°C)

APPLICATIONS:

Open Chain Lubricant is ideal for chain drives of all sizes. It may also be used on wire ropes up to 2" in diameter. (For larger ropes use Whitmore's Wire Rope Lubricant). Open Chain Lubricant is packaged in a variety of containers as well as convenient aerosol spray to suit any application. Whitmore's Open Chain Lubricant may be applied either by dipping, spraying or dripping.

ASTM #		TYPICAL CHARACTERISTICS
	ISO Grade	32
D-445	Kinematic Viscosity cSt @ 40°C cSt @ 100°C	32 6
D-2162	Saybolt Viscosity SUS @ 100°F SUS @ 210°F	152 44
D-2270	Viscosity Index	105
D-97	Pour Point, °F (°C)	-35 (-37)
Gardner Method	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C)	7.32 0.879
D-92	Flash Point, °F (°C) Cleveland Open Cup	375 (191)
D-92	Fire Point, °F (°C) Cleveland Open Cup	410 (210)
D-2783	Four Ball EP Weld Point, kg	200
D-4172	Four Ball Wear Scar Width, mm @ 40 kgf	0.36
D-665	Rust Test Distilled Water Synthetic Sea Water	Pass Pass
D-130	Copper Strip Corrosion 212°F (100°C) @ 3 hr	1B

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Drums	Kegs	Pails	Aerosol Cans 12 per case
-------	------	-------	-----------------------------

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108

An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.