



TECHNICAL DATA SHEET

PARAGON™ SYNTHETIC BLEND ENCLOSED GEAR OIL

Extreme pressure protection is assured with Paragon™ Synthetic Blend Enclosed Gear Oil, even under the most severe conditions of high load, shock load, and reversing motion. Paragon™ Synthetic Blend Enclosed Gear Oil was designed for use in steel-on-steel as well as steel-on-bronze gearing applications such as worm gears. It may also be used to replace compounded oils.

Enclosed gearing systems in surface mining and mineral processing equipment are subjected to unique and demanding operating conditions. Whitmore's Paragon™ Synthetic Blend Enclosed Gear Oil is formulated specifically for tough mining and industrial applications.

Paragon™ Synthetic Blend is designed for use in mining equipment, yet the benefits translate well into almost any industrial application, especially where equipment is subjected to severe conditions or elevated temperatures.

Paragon™ Synthetic Blend Enclosed Gear Oil offers longer service life with reduced oxidation. Advanced wear protection is achieved by the use of a synergistic blend of synthetic fluids and additive compounds designed for extreme pressure performance.

Paragon™ Synthetic Blend Enclosed Gear Oil contains special rust and corrosion inhibitors. Shear resistant polymers allow Paragon™ Synthetic Blend Enclosed Gear Oil to cling to idle gearing during shutdown. This assures a protective coating during start-up.

BENEFITS:

- **EXTREME PRESSURE** - meets the demands of heavily loaded industrial gears and bearings.
- **ANTIFOAM** - protects seals, lowers temperatures, and aids in extending oil life.
- **OXIDATION RESISTANT** – increases service life of oil. Reduces disposal.
- **TACKY** - allows a protective film of lubricant to cling to gearing surfaces even during long shutdowns.

APPLICATIONS:

Paragon™ Synthetic Blend Enclosed Gear Oil is designed for use in heavily loaded enclosed gearing systems such as draglines, shovels, drills, pulverizers, mills, and other severe applications. Paragon™ is also ideal for planetary drive systems on today's newer mining equipment.

Reduces pitting and spalling on heavily loaded plain and antifriction bearing such as extruder thrust bearings (plastics industry), crusher bearings (cement) and roll neck bearings (primary metals industry).

ASTM #		TYPICAL CHARACTERISTICS				
	ISO Grade	220	320	460	680	1000
D-445	Kinematic Viscosity cSt @ 40°C cSt @ 100°C	220 21.8	320 28.5	460 40.5	680 49.0	1,000 65.0
D-2270	Viscosity Index	119	121	136	124	128
D-97	Pour Point, °F (°C)	-22 (-30)	-22 (-30)	-22 (-30)	-22 (-30)	-20(-29)
Gardner Method	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C)	7.28 0.87	7.28 0.87	7.28 0.87	7.28 0.87	7.28 0.87
D-2782	Timken OK Load, lb	65	65	65	65	65
D-2783	Four Ball EP, Weld Point, kg	315	315	315	315	315
D-4172	Four Ball Wear, Scar Width, mm @ 40 kgf	0.35	0.35	0.35	0.35	0.35
D-665	Rust Test Distilled Water Synthetic Sea Water	Pass Pass	Pass Pass	Pass Pass	Pass Pass	Pass Pass
D-130	Copper Strip Corrosion	1B	1B	1B	1B	1B

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Shuttle Tanks	Nonreturnable Totes	Drums	Kegs	Pails
---------------	---------------------	-------	------	-------

THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.