



# TECHNICAL DATA SHEET

## SURE-FILM™ LF EXTREME PRESSURE GREASE

Sure-Film™ LF is a robust lithium 12-hydroxystearate soap base lubricant, designed with the needs of mining equipment in mind, and reinforced with extreme pressure and load carrying additives.

### BENEFITS:

- Retention in Bearings – Does not exhibit high leakage.
- Water Resistance – Will withstand water washout.
- Mechanical Stability – Works continuously without change in consistency.
- Reversibility – Stable with repeated heating and cooling.
- Pressure Oil Separation – Resists oil-soap separation under pressure.
- Compatibility – Compatible with seals.

### APPLICATIONS:

Recommended for use in antifriction ball and tapered roller bearings, bushings, splines, couplings and pins and cable sockets on draglines and shovels. Also recommended for use on rolling stock.

ASTM #	Grade	TYPICAL CHARACTERISTICS		
		0	1	2
D-217	Cone Penetration (Worked)	345-375	300-330	255-285
D-2265	Dropping Point, °F (°C)	340 (171)	355 (179)	365 (185)
D-445	Kinematic Viscosity (Base Oil)			
	cSt @ 40°C	218	218	218
	cSt @ 100°C	16.3	16.3	16.3
Gardner Method	Density, lb/gal @ 60°F (15.5°C)	7.60	7.76	7.80
D-2509	Timken OK Load, lb	45	45	45
D-2596	Four Ball EP			
	Weld Point, kg	315	315	315
	Load Wear Index	50	50	50
D-2266	Four Ball Wear			
	Scar Width, mm	0.50	0.50	0.50
D-1743	Rust Test	Pass	Pass	Pass
	Thickener Type	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate
OEM Standard	Low Temperature Pumpability			
	Lincoln Ventmeter @ 400 psi, °F (°C)	5 (-15)	30 (-1)	45 (7)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

### PACKAGING

Drums	Kegs	Pails
-------	------	-------

### THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108  
An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <http://www.whitmores.com>

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.