

Issuing Date 21-Sep-2018

Revision Date 11-Feb-2019

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION**Product identifier****Product Name** ENVIROLUBE®EXTREME HEAVY**Other means of identification****(M)SDS Number** 1477724**Recommended use of the chemical and restrictions on use****Recommended Use** For industrial use only**Uses advised against** No information available**Details of the supplier of the safety data sheet****Supplier Identification** Whitmores Manufacturing, LLC.**Address** Whitmore Manufacturing
930 Whitmore Drive
Rockwall, Texas USA 75087**Telephone** US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108**E-mail** Sales@whitmores.com**Emergency telephone number****Company Emergency Phone Number** 1-800-699-6318**Emergency Telephone Number** CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)**2. HAZARDS IDENTIFICATION****Classification**

Carcinogenicity	Category 1B
Aspiration toxicity	Category 1

Appearance Dark Brown**Physical state** Semi-Solid**Odor** Mild Petroleum

GHS Label elements, including precautionary statements

Danger

Hazard statements

May cause cancer
 May be fatal if swallowed and enters airways



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful if swallowed Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical Name	CAS-No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Asphalt	8052-42-4	50-55	-	-
Asphalt, oxidized	64742-93-4	15-20	-	-
Alkanes, C18- 28, chloro	85535-86-0	10-15	-	-
Naphtha (petroleum), heavy aromatic	64742-94-5	10-15	-	-
Zinc, bis[O,O-bis(2-ethylhexyl)	4259-15-8	<2	-	-

phosphorodithioato-S,S']-, (T-4)-				
1-Butene, polymer with ethene and 1-propene	25895-47-0	<2	-	-
1-Methylnaphthalene	90-12-0	<2	-	-
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	<1	-	-
Naphthalene	91-20-3	<0.5	-	-
Chlorinated hydrocarbons (chlorinated paraffins)	63449-39-8	<0.5	-	-

4. FIRST AID MEASURES

First aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Ingestion	Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical No information available.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min



1-Methylnaphthalene 90-12-0	TWA: 0.5 ppm S*	-		
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral		
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³	
Chemical Name	Alberta	British Columbia	Ontario TWAEV	Quebec
Asphalt 8052-42-4	TWA: 5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 5 mg/m ³
1-Methylnaphthalene 90-12-0		TWA: 0.5 ppm Skin	TWA: 0.5 ppm Skin	
Naphthalene 91-20-3	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³ Skin	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm Skin	TWA: 10 ppm TWA: 52 mg/m ³ STEL: 15 ppm STEL: 79 mg/m ³

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection If splashes are likely to occur, wear safety glasses with side-shields.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Semi-Solid
Appearance Dark Brown
Odor Mild Petroleum
Color Dark brown
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	



Boiling point / boiling range	No data available	None known
Flash Point	>90.556°C	Open cup
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.02	None known
Water Solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	No information available	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other Information</u>		
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	None known based on information supplied.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.



Skin contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,799.90 mg/kg

Unknown acute toxicity No information available

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	Inhalation LC50
Asphalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Asphalt, oxidized	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	
Naphtha (petroleum), heavy aromatic	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)-	= 3100 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	
1-Methylnaphthalene	= 1840 mg/kg (Rat)		
Petroleum distillates, hydrotreated heavy paraffinic	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	
Naphthalene	= 490 mg/kg (Rat) = 1110 mg/kg (Rat)	> 20 g/kg (Rabbit) = 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Chlorinated hydrocarbons (chlorinated paraffins)	= 26100 mg/kg (Rat) > 21500 µL/kg (Rat)	> 10 mL/kg (Rabbit)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt, oxidized 64742-93-4	-	Group 2A	-	X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Chlorinated hydrocarbons (chlorinated paraffins) 63449-39-8	-	Group 2B	-	-



Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

- Reproductive toxicity** No information available.
- STOT - single exposure** No information available.
- STOT - repeated exposure** No information available.
- Aspiration hazard** May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Asphalt, oxidized	72h EC50: = 56 mg/L (Pseudokirchneriella subcapitata)		-	
Naphtha (petroleum), heavy aromatic	72h EC50: = 2.5 mg/L (Skeletonema costatum)	96h LC50: = 41 mg/L (Pimephales promelas) 96h LC50: = 45 mg/L (Pimephales promelas) 96h LC50: = 1740 mg/L (Lepomis macrochirus) 96h LC50: = 2.34 mg/L (Oncorhynchus mykiss) 96h LC50: = 19 mg/L (Pimephales promelas)	-	48h EC50: = 0.95 mg/L
Zinc, bis[O,O-bis(2-ethylhexyl)phosphorodithioato-S,S']-, (T-4)-	96h EC50: 1.0 - 5.0 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 1.0 - 5.0 mg/L (Pimephales promelas) 96h LC50: 10.0 - 35.0 mg/L (Pimephales promelas)	-	48h EC50: 1 - 1.5 mg/L
Petroleum distillates, hydrotreated heavy paraffinic		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)	-	48h EC50: > 1000 mg/L
Naphthalene	72h EC50: = 0.4 mg/L (Skeletonema costatum)	96h LC50: = 31.0265 mg/L (Lepomis macrochirus) 96h LC50: 5.74 - 6.44 mg/L (Pimephales promelas) 96h LC50: 0.91 - 2.82 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.6 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.99 mg/L (Pimephales	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h	48h EC50: = 1.96 mg/L 48h LC50: = 2.16 mg/L 48h EC50: 1.09 - 3.4 mg/L



		promelas)		
Chlorinated hydrocarbons (chlorinated paraffins)		96h LC50: > 300 mg/L (Lepomis macrochirus) 96h LC50: > 0.0109 mg/L (Oncorhynchus mykiss) 96h LC50: 94.5 - 271 mg/L (Oncorhynchus mykiss) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: > 0.1 mg/L (Lepomis macrochirus)	-	24h EC50: = 102 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Asphalt	6
Naphtha (petroleum), heavy aromatic	6.1
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)-	2.86
Naphthalene	3.6
Chlorinated hydrocarbons (chlorinated paraffins)	6

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one	



			to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S'], (T-4)-4259-15-8	Toxic
Naphthalene 91-20-3	Toxic

14. TRANSPORT INFORMATION

DOT Proper Shipping Name Hazard Class	NOT REGULATED NON-REGULATED N/A
TDG	Not regulated
MEX	NOT REGULATED
ICAO	NOT REGULATED
IATA Proper Shipping Name	Not regulated NON REGULATED
IMDG	Not regulated
RID	NOT REGULATED
ADR	NOT REGULATED
ADN	NOT REGULATED

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Complies.
DSL/NDSL	Complies.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend



TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	Weight-%	SARA 313 - Threshold Values %
Asphalt - 8052-42-4	8052-42-4	50-55	0.1
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)- - 4259-15-8	4259-15-8	<2	1.0
Naphthalene - 91-20-3	91-20-3	<0.5	0.1

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S']-, (T-4)- 4259-15-8		X		
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Naphthalene 91-20-3	100 lb 1 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Naphthalene - 91-20-3	carcinogen, 4/19/2002
Chlorinated hydrocarbons (chlorinated paraffins) - 63449-39-8	Carcinogen



U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Asphalt 8052-42-4	X	X	X		X
Asphalt, oxidized 64742-93-4	X				X
Zinc, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S`]-, (T-4)- 4259-15-8	X		X	X	
1-Methylnaphthalene 90-12-0	X	X	X		
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7					X
Naphthalene 91-20-3	X	X	X	X	X
Chlorinated hydrocarbons (chlorinated paraffins) 63449-39-8		X			X

16. OTHER INFORMATION

NFPA **Health hazards** 2 **Flammability** 1 **Instability** 0 **Physical and Chemical Properties -**
HMIS **Health hazards** 2 * **Flammability** 1 **Physical hazards** 0 **Personal Protection** X
Chronic Hazard Star Legend * = *Chronic Health Hazard*

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 21-Sep-2018

Revision Date 11-Feb-2019

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

